

Yüksek Performanslı Hidrolik Tork Pompaları

High Performance Electric Driven Hydraulic Torque Pumps



EP Series



- › Maksimum 700 bar (10.000 Psi) çalışma basıncı
- › Ø 100mm Bar/Psi göstergeli, kalibrasyonlu manometre
- › Gelişmiş manyetik motor yapısı ile 3 kat daha uzun ömür
- › 1.125 ve 1.50 HP motor gücü seçeneği ile hızlı torklama
- › Motoru ve elektronik parçaları koruyan sert plastik kılıf
- › Endüstriyel kullanıma uygun ergonomik kontrol kumandası
- › Kademesiz ayarlanan ekstra güvenli basınç ayar valfi
- › Opsiyonel çoklu tork anahtarı bağlama seçeneği
- › 3.8 ve 9.5 litre kapasiteli sağlam hidrolik yağ tankı
- › Kolay gözlenebilir yağ seviyesi göstergesi
- › Türkiye'de servis, yedek parça ve kalibrasyon hizmetleri
- › *Maximum working pressure 700 Bar (10.000 Psi)*
- › *Ø 100mm calibrated gauge display shows PSI and Bar*
- › *3x longer life with improved magnetic motor driving*
- › *1.125 and 1.50 HP motor power options for fast operation*
- › *Electronics are enclosed in a safety shroud to protect pump*
- › *Ergonomic and rugged remote operation pendant (5m)*
- › *Stepless adjustable extra safety pressure regulating valve*
- › *Optional add-on for connect multiple torque wrenches*
- › *Durable and lightweight aluminum oil tank (3.8 and 9.5 litres)*
- › *Sight glass enables operator to monitor reservoir oil levels*
- › *Repair, maintenance and calibration services*

Parça Part	Valf Tipi Valve Style	Motor Gücü Power	Debi (litr/dk) Flow Rate (l/min)	Yağ Kapasitesi Oil Capacity	Ağırlık Weight	Ölçüler (mm) Dimensions	Bağlanabilir Cihaz Sayısı
No.	#	HP	@ 75 bar @ 700 bar	ltr	kg	A B C D	Multi Tool
EP500-230V	Otomatik Geri Dönüş Auto Retract	1,125	8,6 0,8	3,8	26,8	330 208 483 145	1
EP1000-230V	Otomatik Geri Dönüş Auto Retract	1,5	11,5 0,9	5,7	33,6	381 221 483 150	1
EP1000-Q-230V	Otomatik Geri Dönüş Auto Retract	1,5	11,5 0,9	9,5	36,7	432 246 483 150	4

Aksesuarlar / Accessories

